NO. DOT-TSC-NHTSA-80-22

DOT-HS-805 482

LIGHT TRUCK CHARACTERISTICS, HISTORICAL DATA BASE

DEPARTMENT OF TRANSPORTATION FEB 2 4 1981

LIBRARY

C. CANTWELL

CHILTON COMPANY
201 King of Prussia Road
Radnor PA 19089



NOVEMBER 1980 FINAL REPORT

DOCUMENT IS AVAILABLE TO THE PUBLIC THROUGH THE NATIONAL TECHNICAL INFORMATION SERVICE, SPRINGFIELD, VIRGINIA 22161

Prepared for

U.S. DEPARTMENT OF TRANSPORTATION

National Highway Traffic Safety Administration
Office of Research and Development
Washington DC 20590

NOTICE

This document is disseminated under the sponsorship of the Department of Transportation in the interest of information exchange. The United States Government assumes no liability for its contents or use thereof.

NOTICE

The United States Government does not endorse products or manufacturers. Trade or manufacturer's names appear herein solely because they are considered essential to the object of this report.

NOTICE

The views and conclusions contained in the document are those of the author(s) and should not be interpreted as necessarily representing the official policies or opinions, either expressed or implied, of the Department of Transportation.

HT542			Technical Report Documentation Pag
1. Report No. DOT-HS-805 482	2. Gov	ernment Accession No.	3. Recipient's Cotolog No.
LIGHT TRUCK CHARACTER HISTORICAL DATA BASE	ISTICS	9	5. Report Dote November 1980
		DEPARTMENT OF TRANSPORTATION	Performing Organization Code B. Performing Organization Report No.
7. Author(s) C. Cantwell		FEB 2 4 1981	DOT-TSC-NHTSA-80-22
9. Performing Organization Name and Add Chilton Company* 201 King of Prussia R		LIBRARY	10. Work Unit No. (TRAIS) HS061/R0427 11. Contract or Grant No.
Radnor PA 19089		CLARGE SECTION	DOT-TSC-1463 13. Type of Report and Period Covered Final Powers
12. Sponsoring Agency Nome and Address U.S. Department of Tr National Highway Traf	fic ^{Sa}	fety Administratio	
Office of Research an Washington DC 20590	d Deve	lopment	14. Sponsoring Agency Code
*Under contract to:	R T	.S. Department of esearch and Specia ransportation Systambridge MA 02142	ll Programs Administration
This report is a desoperating performance for the model years 19 DOT/TSC DEC System 10 published and unpublished when raw decing made w	, and m 955 thi compu shed so	market characteris rough 1977, which ter system. Infor ources with extrap	tics of light trucks
using production volumission and GVWR class vehicle configurations	me, modes attri- s. Modes n of a ed by a	del, body type, en ibutes as criteria dels which are ess manufactureri.e attributes of only	uped by manufacturer, gine displacement, trans- to select representative entially duplicated by ., Chevrolet C-10 and GMC one of the duplicate then combined.
Characteristics are U.S. sales of domestic indicated.	docume and	ented for vehicles imported light tru	representative of total cks for the model years
17. Key Words		18. Distribution Ste	otement
Light Truck Characteristics, Data I	Base	THRO	IMENT IS AVAILABLE TO THE PUBLIC DUGH THE NATIONAL TECHNICAL RMATION SERVICE, SPRINGFIELD, INIA 22161
19. Security Classif. (of this report) Unclassified		Security Clossif. (of this page) Inclassified	21. No. of Pages 22. Price 65



PREFACE

The work in this report is aimed at providing an information base on light truck characteristics. This report updates information in a previously published report: "Light Duty Truck Characteristics, Historical Data Base," Report Number DOT-TSC-NHTSA-79-37, December, 1979.

METRIC CONVERSION FACTORS

	Sy. (bz.)	11	e P ī	i	,	T T T			5 2		E L	5 }	ir.	P			•		
Meesures	To Gind	inches	fact yards			square inches square yards square miles	90798		ounces pounds short tone	:	pints	querte	cubic feet	cubic yands			Fabranhelt temperature	001	00 06 01
ions from Metric	Muttiply hy LENGTH	0.96	3.5 1.1	9 .	AREA	9.19	%	MASS (weight)	2.2	VOLUME	2,1	8.5	35	1.3		TEMPERATURE (exect)	9/5 (then add 32)	021 08	20 40
Appreximete Conversions from Metric Mesures	When You Know	mellimaters cantimaters	moters	N I COND FOR O		squere continuoters squere metere	hectares (10,000 m²)	M	grame kilopiams tornes (1000 kg)		millilitære liters	liters	cubic metere	cubic metere		LEMP	Celsius	1 }	-40 -20 0
	Symbol	nen Cm	E E .	5		`B~e^}	2		.2.		Ē -	_	- ^€	Ē		`	٠	* 64 T	7
53	ZZ IZ 01	z 61	1 1 1		91 			ET 2				 		•	1	'l' '		''' '' ''	
	4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4			e 5		~ _€ ~ _€	~ _E ~g	e 4	0 d -		ĒĒ			_	- [~] E			0 1	
Meeseres	To Find St		Centimaters	meters hilometers		aguare Centimaters Square metere	square meters	hecures	grams hilograms tomas		millilitere	millelitere.	liers liers	liters	Litera Cubic metera	cubic meters			labins, see NBS Misc., Publ. ('80.
Appreximete Conversions to Metric Messures	Mattiply by	LENGTH	-2.5 30	6.0	AREA	8.8 0.09	0.8 2.6	MASS (weight)	20 0.45 0.9	VOLUME	a ž	30	0.24	0.95	3.8	97.0	TEMPERATURE (exect)	5/9 (after subtracting 32)	D Calabet No. C13.10 286,
Approximete Con-	When Yes Know		inchae	yards		square inches	square yarde		ounces pounds short tons		tenspoons tablescoone	fluid owncoo	Cups	querte	gellons cubic feet	cubic yards	TEMP	Fahranheit temperature	"1 in 1 2.54 (macHy), Fin infer exact conversions and insur-straind ables, see NBS Units of Weights and Measures, Price \$2.25, SD Catalon Nii. C.3.10 286.
	Sympol					~2 °.2	€ر قر				tup	fl or			9.	, o			in 1 2.54 to

TABLE OF CONTENTS

<u>S</u>	ection		<u>Pag</u>	zе
	1.	INTRO	ODUCTION	L
		1.1 1.2 1.3 1.4	Background	1 1 2 2
	2.	METHO	ODOLOGY	5
			General	_
			2.2.1 Selection Parameters 5 2.2.2 Selection Example 7	
		2.3		5
			2.4.2 Fuel Economy 2	6 7 9
		2.5	Attribute Information Sources 3	2
			2.5.1 Delineation of Production Sources 33 2.5.2 Compatability with Published Information. 33	
		2.6	Collation and Data Processing 39	9
	3.	CONCI	LUSIONS55	5
	4.	RECON	MMENDATIONS 57	7
		APPEN	NDIX A - REPORT OF NEW TECHNOLOGY)

LIST OF ILLUSTRATIONS

Figure		Page
2-1.	MANUFACTURERS PRODUCTION DATA COLLECTION SHEET - DODGE	. 12
2-2.	MANUFACTURERS PRODUCTION DATA COLLECTION SHEET - PLYMOUTH	. 13
	LIST OF TABLES	
<u>Table</u>		Page
2-1.	PRODUCTION TOTALS	. 7
2-2.	COMBINED PRODUCTION TOTAL	. 8
2-3.	INITIAL NINE (9) CONFIGURATIONS FOR 1976 DODGE/PLYMOUTH VANS	. 9
2-4.	FINAL VEHICLE CONFIGURATIONS SELECTED FOR 1976 DODGE/PLYMOUTH VANS	. 10
2-5.	HORSEPOWER AND TORQUE CORRECTION FACTORS - GROSS TO NET HORSEPOWER	. 30
2-6.	ATTRIBUTE INFORMATION SOURCE	. 34
2-7.	STRUCTURE DEFINITION SHEET	. 40
2-8.	FILE DESCRIPTION	. 41
2-9.	ATTRIBUTE CODE LIST	. 48
2-10.	CODE TABLES	. 52
2-11.	BODY CLASS DEFINITIONS DOT LIGHT TRUCK DATA BASE	. 54

LIST OF ABBREVIATIONS

Abbreviation	<u>Definition</u>
AM	Amplitude Modulation
CID	Cubic Inch Displacement
EPA	Environmental Protection Agency
FM	Frequency Modulation
GVWR	Gross Vehicle Weight Rating
LT	Light Truck(s)
MPH	Miles per hour
NA	Not Applicable
N/V	Ratio of engine speed (RPM) to
	vehicle speed (MPH)
RPM	Revolutions per minute

Standard

Transportation Systems Center

Wheel Drive as 2 Wheel Drive

STD

TSC

WD

	.*
	•
,	

INTRODUCTION

1.1 GENERAL

The information presented and discussed in this report is the result of an extensive, in-depth research effort directed toward the compilation of pertinent information relating to all domestic and imported light trucks sold in the United States during the 1955 through 1977 model years.

The information produced by this research project constitutes an historical data base similar to the TSC data base previously developed for passenger cars.* This historical data base may be used as a means of defining light truck characteristics during the time period covered by the project (1955 to 1977 inclusive).

The background, scope, limitations, methodology, conclusions and recommendations sections follow.

1.2 BACKGROUND

Light trucks (10,000 1b. GVWR and below), have undergone many changes since 1955. The changes have ranged from subtle styling alterations to proliferations of models, body types, drivetrain variations, and accessory options. These changes have created a need to understand what changes have occured during the past several years. Such knowledge, coupled with additional knowledge in areas such as prevailing economic forces, transportation regulations, etc., can be used to predict what may happen to this light truck market as influencing factors change.

^{*} Milne, J.A., C. Cantwell, and H. Eissler, "Automobile Characteristics, Historical Data Base," Chilton Co. under contract to U.S. Department of Transportation, Transportation Systems Center, Report No. DOT-TSC-OST-77-12/PB-272 746, August 1977.

1.3 SCOPE

The objective of this project is to procure and present data of the physical, operating, performance, and production characteristics of light trucks. The data are gathered for all domestically manufactured and imported light trucks that were sold in the United States during the 1955 through 1977 model years. Each vehicle configuration is defined by over 60 attributes.

The work is divided into two main areas. The first area includes vehicle selection, attribute selection, attribute definitions, and format. The second area includes data collection, correlation, and collation. Data is presented on tape and is loaded into the DOT/TSC DEC10 Computer System.

The information was gathered from trade publications, direct contact with manufacturers, unpublished sources, specialized testing reports, the Environmental Protection Agency, and trade associations.

1.4 LIMITATIONS

The lack of published sources of information for certain attributes necessitated the use of unpublished, but reliable, sources (such as Auto Manufacturers Data Books), and some extrapolation or expansion of hard data. The model year 1977 sales figures are projected since the completion date of the project is prior to the end of the model year. Accessory attributes could not be aligned with a particular model/engine/transmission configuration, so they apply to the model configuration as a whole.

No EPA fuel economy data were available for the 1972 model year for light trucks. Some road-test mileage information was used in the few instances where the tested configuration matched a configuration of this study. When used, technical judgements were applied to match the road test data to the 1975 EPA CVS-1 cycle. No fuel economy data were available from the EPA for GVWR configurations over 6,000 pounds. There is less available EPA fuel economy data for 1975 Ford vehicles than for other

major manufacturers. Some road test data were used to supplement the EPA 1975, 1976, and 1977 data, but this use was minimal. Data presented in the data base reflect these limitations.

£*	
	•

METHODOLOGY

2.1 GENERAL

The light truck is a complex and diverse vehicle, intended for a multitude of utilitarian and recreational activities.

These many uses create a potential for engine/transmission/model configurations that number into the thousands for each model year. The incorporation of every engine/transmission/model configuration into the data base is beyond the scope of this project. However, the requirements for the data base allow a selected vehicle sampling to represent a specific model year fleet. All domestic and imported vehicles that fit the requirements are included in the data base for the model years 1955 through 1977.

For the following discussion, a vehicle "make" refers to a manufacturer, and a vehicle "model" refers to a vehicle series designation of that manufacturer: for example, Ford, Dodge, and Chevrolet are makes, and Ford F100, Dodge D100, and Chevrolet C10 are models.

2.2. VEHICLE SELECTION

2.2.1 Selection Parameters

The parameters used for selecting the vehicle configurations representing each of the model years used in the data base are as follows:

- (a) All models manufactured domestically whose sales exceed 2500 units annually.
- (b) All models of imported light trucks whose sales exceed 15,000 units annually.

(c) The most popular model of imports whose sales are between 2,000 and 15,000 units annually.

Imports and domestic vehicles, other than the above, with sales of less than 2,000 units, are excluded.

Vehicle configurations are determined by model identification, engine, and transmission, i.e., D100, 318V8, 3 Speed Automatic. Vehicles manufactured by two or more divisions of the same corporation are combined (i.e., Chevrolet C10/GMC C-1500) if they are essentially the same vehicle, and are listed as a single vehicle in the data base. Both model names or identification numbers are listed in the model name attribute to simplify identification.

Individual vehicle configurations with a production volume of 2500 units or more are included in the data base. Passenger and cargo van versions of the same model are maintained as separate configurations throughout the data base. Suburban and pickup versions of the same model are also recorded separately for passenger and cargo vans, suburban and pickup trucks and for four-wheel drive and two-wheel drive versions of the same vehicle.

Similar body configurations within a model series are grouped, and one body configuration is used to represent the group, i.e., with stepside and fleetside pickups, fleetside is used as the representative vehicle.

Models whose GVWR start at or near 10,000 lbs. and go well beyond (i.e., 14,000 lbs.) are excluded from the data base.

Cab and chassis units are combined with their pickup counterparts to form a single configuration, and Cutaway vans are combined with their van counterparts.

High-cube van configurations are shown separately only if production volume warrants. This rarely occurred in the data base. Otherwise, they are combined with normal vans.

Suburban type vehicles include and combine both 2-and 4-door versions. Motor home chassis are excluded from the data base.

When there are models available in more than three wheel-bases, and the use of one wheelbase, which is basically the same as one of the other wheelbases, is very low, then the two are combined. For example, if a Ford 159-inch wheelbase is seven percent, and a Ford 161-inch wheelbase is one percent, then a Ford 159-inch wheelbase is listed instead as eight percent.

A configuration of a vehicle available in both two and four-wheel drive is shown as one vehicle configuration. Attribute values, which vary between the two and four-wheel drive versions, and the production volumes of these versions are listed separately and identified by drive version.

Vehicle model configurations, produced by manufacturers with low model year production totals that fall below the 2,500 minimum, are represented by at least one configuration in order to give that coporation proper representation. The exception is Studebaker because total production of all models falls below 2,500 units.

2.2.2 Selection Example

The following example illustrates the vehicle selection process in detail.

For the 1976 model year, the Plymouth and Dodge Divisions of Chrysler Corporation offered virtually identical trucks. The Dodge version is known as the B-100 truck and is available in a cargo (Tradesman) and passenger (Sportsman) configuration. The Plymouth version is known as PB100 Voyager and is only available in a passenger version. Table 2-1 describes the initial configuration selection process.

	TABLE 2-1.	PRODUCTION T	OTALS
1976	Dodge B-100 (Van)	1976	Plymouth PB100 Voyager
	Cargo (Tradesman)	34889	N.A.
	Passenger (Sportsman)	3897	2103
	Total	38786	2103

Table 2-2 shows the combined production total that is obtained by applying the rule of selection which states that vehicles manufactured by two or more divisions of the same corporations are combined if they are essentially the same vehicle.

TABLE 2-2. COMBINED PRODUCTION TOTAL

Dodge/Plymouth B-Truck (Van)

Dodge + Plymouth = Combined

Cargo 34,889 + 0 = 34,889

Passenger 3,897 + 2103 = 6,000

Total 38,786 + 2103 = 40,889

Referring to Figures 2-1 and 2-2, The Manufacturers Production Data Collection Sheets (see pp 11 and 12), it can be seen that the Dodge/Plymouth Van has three possible engines and three possible transmissions, giving a total possible vehicle line representation of nine. The Dodge/Plymouth Van is available in two variations, a passenger and a cargo configuration. All engines and all transmissions are available in both configurations, which brings the possible total representative vehicles to 18. If the rule is applied that states that Van models available in cargo and passenger configurations are combined and the attributes peculiar to each configuration and their production volumes are listed separately, then nine (9) configurations represent these vehicles as shown in Table 2-3.

All configurations over 2500 units are represented separately in the data base. Cargo and passenger versions of the same van configuration are combined into one configuration, but the production total for each version is listed separately. Referencing Table 2-3, it is seen that these rules would provide for the combination of lines 1 and 2 with 225M3 configuration representing this combination. Similarly, lines 4 and 5 and lines 7, 8, and 9 are combined. The rules would permit the further combination of

TABLE 2-3. INITIAL NINE (9) CONFIGURATIONS FOR 1976 DODGE/PLYMOUTH VANS.

			Production	
Line	*Engine/Transmission	Total	Cargo	Passenger
1.	225M3	5314	4974	340
2.	225M4	133	111	22
3.	225A3.	10044	8731	1313
4.	318M3	8003	7209	794
5.	318M4	207	160	47
6.	318A3	15816	12657	3159
7.	360M3	441	377	64
8.	360M4	13	8	5
9.	360A3	918	662	256

^{* 255=255} CID engine; M3 = 3 speed manual transmission;
A3 = 3 speed automatic

the 360 CID vehicles (lines 7, 8 and 9) with the 318A3 vehicles. However, in the interest of maintaining maximum engine representation, the 360 CID engine is represented in the data base also. The resulting five configurations used to represent the 1976 Dodge/Plymouth vans are shown in Table 2-4. This table also shows the production volumes for the cargo and passenger versions.

The vehicles listed in Table 2-4 are those that appear in the data file and for which all information is given.

In every case, as vehicle model configurations are combined, the total production of the model and model/engine configuration is maintained. Also, in every case, the broadset vehicle model/engine configuration representation is maintained.

TABLE 2-4. FINAL VEHICLE CONFIGURATIONS SELECTED FOR 1976 DODGE/PLYMOUTH VANS

*Engine/Transmission	Production Totals					
	Cargo	Passenger				
225M3	5085	362				
225A3	8731	1313				
318M3	7369	841				
318A3	12657	3159				
360A3	1047	325				
Total	34889	6000				

^{* 225 = 225} CID engine; M3 = 3 speed manual transmission;
A3 = 3 speed automatic.

Data collection sheets compiled from manufacturers' production records are referenced for all years of Dodge, Plymouth, Ford, and all import cars. The years 1975, 1976, and 1977 for AMC and International, and 1976 and 1977 for Chevrolet/GMC are also supported by these data collection sheets.

Where data for data collection sheets were not available, the best available published and unpublished sources were used to determine production volumes and option penetrations, i.e., Wards Automotive Yearbooks, Automotive News, Almanac Issues, and Motor Vehicle Manufacturers Association (M.V.M.A.) statistical reports. In a very few cases judgement had to be employed to determine production quantities for a specific configuration such as production models which a manufacturer may lump together because of the similarity of the vehicles (i.e., P10, P20, P30 Chevrolet Parcel delivery vans) or for lack of recorded data.

The use of the manufacturers' production data collection sheet is described below.

The data collection sheet contains information relating to the production totals and option penetrations of the light truck listed at the top of each sheet. The information contained on these sheets was obtained directly from the manufacturers, rather than published sources, in order to obtain the highest degree of accuracy. The data collection sheet information was used as input for the data recording sheets wherever applicable. The information on the data collection sheets was used to fill the appropriate attributes as well as to assist in the final vehicle selection. The following is a detailed example of how the data sheet was employed and which attributes it filled.

Refer to Figures 2-1 and 2-2, Manufacturers' Production Data Collection Sheets for Dodge and Plymouth. Data sheet lines A, 1-7 were used to determine the final vehicle selection and as such fills the following attributes for the 1976 Dodge/Plymouth van. See Section 2.3 for attribute definitions.

Line A - fills attributes

- 03) Model Name Cargo Van
- 04) Model Name Passenger Van for all final vehicles.

Lines 2, 3 or 4 fill attributes

- 09) Cubic inch displacement
- 10) Number of cylinders and arrangement.

Lines 5, 6 or 7 fill attribute

06) Transmission type and number of gears.

Lines 8-11 fill attributes

- 17) Wheelbase 1
- 18) Percent of sales Wheelbase 1
- 19) Wheelbase 2
- 20) Percent of sales Wheelbase 2
- 21) Wheelbase 3
- 22) Percent of sales Wheelbase 3 for each of the vehicles.

C.I.D. 4 Cyl.	A. 1)	76B 100-Tradesman/Sportsm Total of Model No. 3878					Percer 10	
2)	-,		-			Total		
3 318 C.I.D. 8 Cyl. 22806 20026* 2780** 58.8 57.4* 69.9**	2)		14700:	13816*	884**	37.9	39.6*	25.3**
4) 360 C.I.D. 8 Cyl. 1280 1047* 233e* 3.3 3.1* 4.8** C.I.D. 8 Cyl. 223e* 3.3 3.1* 4.8** C.I.D. 8 Cyl. 228.0 36.0* 19.0** 5) 3 Sp. Manual 28.0 36.0* 19.0** 6) 4 Sp. Manual 1.3 .8* 1.0** 7) Automatic 70.7 63.2* 80.0** 8) 109 Inch WB 27833:26047* 1786** 71.8 9) 127 Inch WB 10953: 8842* 2111** 10) 127X Inch WB 10953: 8842* 2111** 11) TOTAL 38786:34889* 3897** 12) Models w/4 WD 8.8 10.0** 13) Cargo Can 34889* 14) Pass. Van 3897** 15) Air Conditioning 6361 16.4 13.8* 39.6** 16) Power Disc Brakes 12062 31.1 25.0* 85.8** 17) Power Steering 28702 74.0 72.0* 92.7** 18) AM Radio 24435 26.3 23.2* 54.0** 19) AM/FM Radio 1784 4.6 3.8* 11.5** of total 4.8 E.R. 1.8 E.R. 5.0 Adjustable Steering 698 E.R. 1.8 E.R. 5.0 Adjustable Steering 698 E.R. 1.8 E.R. 5.0 Adjustable Steering 65.5* - 100 Tinted Glass 2521 6.5* - 4800 32.1 31.5* 37.7**		C.I.D. 6 Cyl.						
C.I.D. 8 Cyl. 5) 3 Sp. Manual C.I.D. 8 Cyl. 6) 4 Sp. Manual 1.3	3)	318 C.I.D. 8 Cyl.	22806	20026*	2780**	58.8	57.4*	69.9**
S S Nanual	4)	360 C.I.D. 8 Cyl.	1280	1047*	233**	3.3	3.1*	4.8**
1.3		C.I.D. 8 Cyl.						
70.7 63.2* 80.0** 8) 109 Inch WB 27833:26047* 1786** 71.8 9) 127 Inch WB 10953: 8842* 2111** 28.2 10) 127X Inch WB	5)	3 Sp. Manual		4 · · · · · · · · · · · · · · · · · · ·		28.0	36.0*	19.0**
109	6)	4 Sp. Manual				1.3	8*	1.0**
127	7)	Automatic				70.7	63.2*	80.0**
10) 127X Inch WB Inch WB 11) TOTAL 38786:34889* 3897** 12) Models w/4 WD N.A. 13) Cargo Can 34889* 14) Pass. Van 3897** 15) Air Conditioning 6361 16.4 13.8* 39.6** 16) Power Disc Brakes 12062 31.1 25.0* 85.8** 17) Power Steering 28702 74.0 72.0* 92.7** 18) AM Radio 24435 26.3 23.2* 54.0** 19) AM/FM Radio 1784 4.6 3.8* 11.5** 20) Interior Trim of Pass Carrier 698 E.R. 1.8 E.R. 1.8 E.R. 1.8 21) Exterior Trim 1862 22) Radial Tire 698 E.R. 1.8 E.R. 1.8 348.7 240 Tinted Glass 2521 6.5A + 16.4w/s 25) GVW Group 4600 61.6 68.5* - 4800 32.1 31.5* 37.7**	8)	109 Inch WB	27833:26047*	1786**			71.	8
Inch WB	9)	127 Inch WB	10953: 8842*	2111**			28.	2
11) TOTAL 38786:34889* 3897** 12) Models w/4 WD	10)	127X Inch WB				à.		
Models w/4 WD		Inch WB	***					
13) Cargo Can 34889* 14) Pass. Van 3897** 15) Air Conditioning 6361 16.4 13.8* 39.6** 16) Power Disc Brakes 12062 31.1 25.0* 85.8** 17) Power Steering 28702 74.0 72.0* 92.7** 18) AM Radio 24435 26.3 23.2* 54.0** 19) AM/FM Radio 1784 4.6 3.8* 11.5** 20) Interior Trim of Pass Carrier of total 4.8 21) Exterior Trim 1862 22) Radial Tire 698 H.R. 1.8 H.R. 5.0 23) Adjustable Steering N.A. 24) Tinted Glass 2521 6.5A + 16.4w/s 25) GVW Group 4600 61.6 68.5* - 4800 32.1 31.5* 37.7**	11)	TOTAL	38786:34889*	3897**				
14) Pass. Van 3897** 16.4 13.8* 39.6** 15) Air Conditioning 5361 16.4 13.8* 39.6** 16) Power Disc Brakes 12062 31.1 25.0* 85.8** 17) Power Steering 28702 74.0 72.0* 92.7** 18) AM Radio 24435 26.3 23.2* 54.0** 19) AM/FM Radio 1784 4.6 3.8* 11.5** 20) Interior Trim of Pass Carrier of total 4.8 21) Exterior Trim 1862 48.7 22) Radial Tire 698 H.R. 1.8 H.R. 5.0 23) Adjustable Steering N.A. 24) Tinted Glass 2521 6.5A + 16.4w/s 25) GVW Group 4600 61.6 68.5* - 4800 32.1 31.5* 37.7**	12)	Models w/4 WD					N.	Α
15) Air Conditioning 6361 16.4 13.8* 39.6** 16) Power Disc Brakes 12062 31.1 25.0* 85.8** 17) Power Steering 28702 74.0 72.0* 92.7** 18) AM Radio 24435 26.3 23.2* 54.0** 19) AM/FM Radio 1784 4.6 3.8* 11.5** 20) Interior Trim of Pass Carrier of total 4.8 21) Exterior Trim 1862 48.7 22) Radial Tire 698 H.R. 1.8 H.R. 5.0 23) Adjustable Steering N.A. 24) Tinted Glass 2521 6.5A + 16.4w/s 25) GWW Group 4600 61.6 68.5* -	13)	Cargo Can	34889*					
16) Power Disc Brakes 12062 31.1 25.0* 85.8** 17) Power Steering 28702 74.0 72.0* 92.7** 18) AM Radio 24435 26.3 23.2* 54.0** 19) AM/FM Radio 1784 4.6 3.8* 11.5** 20) Interior Trim of Pass Carrier of total 4.8 21) Exterior Trim 1862 48.7 22) Radial Tire 698 H.R. 1.8 H.R. 5.0 23) Adjustable Steering N.A. 24) Tinted Glass 2521 6.5A + 16.4w/s 25) GVW Group 4600 61.6 68.5* - 4800 32.1 31.5* 37.7**	14)	Pass. Van	3897**					
17) Power Steering 28702 74.0 72.0* 92.7** 18) AM Radio 24435 26.3 23.2* 54.0** 19) AM/FM Radio 1784 4.6 3.8* 11.5** 20) Interior Trim of Pass Carrier of total 4.8 21) Exterior Trim 1862 48.7 22) Radial Tire 698 H.R. 1.8 H.R. 5.0 23) Adjustable Steering N.A. 24) Tinted Glass 2521 6.5A + 16.4w/s 25) GVW Group 4600 61.6 68.5* - 4800 32.1 31.5* 37.7**	15)	Air Conditioning	5361	······································	16.4		13.8*	39.6**
18) AM Radio 24435 26.3 23.2* 54.0** 19) AM/FM Radio 1784 4.6 3.8* 11.5** 20) Interior Trim of Pass Carrier of total 4.8 21) Exterior Trim 1862 48.7 22) Radial Tire 698 H.R. 1.8 H.R. 5.0 23) Adjustable Steering N.A. 24) Tinted Glass 2521 6.5A + 16.4w/s 25) GVW Group 4600 61.6 68.5* - 4800 32.1 31.5* 37.7**	16)	Power Disc Brakes	12062		31.1		25.0*	85.8**
19) AM/FM Radio 1784 4.6 3.8* 11.5** 20) Interior Trim of Pass Carrier of total 4.8 21) Exterior Trim 1862 22) Radial Tire 698 H.R. 1.8 H.R. 5.0 23) Adjustable Steering N.A. 24) Tinted Glass 2521 6.5A + 16.4w/s 25) GVW Group 4600 61.6 68.5* - 4800 32.1 31.5* 37.7**	17)	Power Steering	28702	· · · · · · · · · · · · · · · · · · ·	74.0		72.0*	92.7**
20) Interior Trim of Pass Carrier 48.7 21) Exterior Trim 1862 22) Radial Tire 698 33) Adjustable Steering 24) Tinted Glass 2521 4600 4800 32.1 6 total 4.8 H.R. 5.0 6 total 4.8 H.R. 5.0 6 total 4.8 6 total 4.8 6 total 4.8 18.	18)	AM Radio	24435		26.3		23.2*	54.0**
21) Exterior Trim 1862 48.7 22) Radial Tire 698 H.R. 1.8 H.R. 5.0 23) Adjustable Steering N.A. 24) Tinted Glass 2521 6.5A + 16.4w/s 25) GVW Group 4600 61.6 68.5* - 4800 32.1 31.5* 37.7**	19)	AM/FM Radio	1784		4.6		3.8*	11.5**
21) Exterior Trim 1862 22) Radial Tire 698 H.R. 1.8 H.R. 5.0 23) Adjustable Steering N.A. 24) Tinted Glass 2521 6.5A + 16.4w/s 25) GVW Group 4600 61.6 68.5* - 4800 32.1 31.5* 37.7**	20)	Interior Trim	of Pass Carrier				of tota	1 4.8
22) Radial Tire 698 23) Adjustable Steering N.A. 24) Tinted Glass 2521 6.5A + 16.4w/s 25) GVW Group 4600 61.6 68.5* - 4800 32.1 31.5* 37.7**	21)	Exterior Trim	1862			48.7		
24) Tinted Glass 2521 6.5A + 16.4w/s 25) GVW Group 4600 61.6 68.5* - 4800 32.1 31.5* 37.7**	22)	Radial Tire	698		H.R. 1.8	3		H.R. 5.0
25) GVW Group 4600 61.6 68.5* - 4800 32.1 31.5* 37.7**	23)	Adjustable Steering		· · · · · · · · · · · · · · · · · · ·			N.	Α
4800 32.1 31.5* 37.7**	24)	Tinted Glass	2521				6.5A +	16.4w/s
	25)	GVW Group	4600		61.6		68.5*	
5200 6.3 - 62.2**			4800		32.1		31.5*	37.7**
			5200		6.3		-	62.2**

^{*}Cargo Van; ***Passenger Van

FIGURE 2-1. MANUFACTURERS' PRODUCTION DATA SHEET - DODGE

A 19	976 PB100 Voyager Model			
1)	Total of Model No. 2103			Percentage 100
	C.I.D. 4 Cyl.			
2)	225 C.I.D. 6 Cyl.	791 + 884 = 1675		37.6
	C.I.D. 6 Cyl.			
3)	318 C.I.D. 8 Cyl.	1200 + 22806 = 24026		58.0
4)	360 C.I.D. 8 Cyl.	92		4.4
	C.I.D. 8 Cyl.			
	C.I.D. 8 Cyl.	-		
5)	3 Sp. Manual	458		21.8
6)	4 Sp. Manual	34		1.6
7)	Automatic	1611		76.6
8)	109 Inch WB	1418		67.4
9)	127 Inch WB	685		32.6
10)	Inch WB			
11)	Inch WB			
12)	Models w/4 WD			000
13)	Cargo Van			
14)	Pass. Van			100
15)	Air Conditioning	595	***************************************	28.3
16)	Power Disc Brakes	1785		84.9
17)	Power Steering	1750	· · · · · · · · · · · · · · · · · · ·	83.2
18)	AM Radio	1129		53.7
19)	AM/FM Radio	164		7.8
20)	Interior Trim			SID
21)	Exterior Trim			STD
22)	Radial Tire	124		5.9
23)	Adjustable Steering			N.A.
24)	Tinted Glass	831	·	39.5A - 11.3w/s
25)	GVW Group Total	4800		54.6
		5200		45.4

FIGURE 2-2. MANUFACTURERS' PRODUCTION DATA COLLECTION SHEET-PLYMOUTH

Line 12 does not apply to the vehicles in the example but is used to determine the final vehicle selection for models available in a 4-wheel configuration.

Lines 13 and 14 indicate the total number of Cargo-Vans and passenger vans for checking purposes (i.e., to determine if recorded engines per vehicle configuration match the total number of that configuration (Cargo or Passenger) produced.)

Line	15	fills	attribute	53)	Air	condi	ition	ning,	percentage
					of	calec	for	each	vehicle

Lines	20	and	21	fill	attributes	69)	Interior		trin	n, per	centage	
							of	sales	for	each	vehicle.	

Line	22	fills	attributes	73)	Steel	belte	ed :	radial	tire	es,
						percen	ntage	of	sales	for	each
						vehic:	le.				

Line 23 does not apply to the vehicle configurations in the example but fills attribute

- 75) Adjustable steering column percentage of sales for each vehicle when applicable.
- Line 24 fills attribute 77) Tinted glass, percentage of sales for each vehicle.

Line 25, generally written in on the reverse side of the sheet, fills attributes

29) GVWR 1

30) GVWR 2

31) GVWR 3

for each vehicle, depending on the number of wheelbases available.

The total result of the Manufacturers' Production Data Collection Sheet is to fill a minimum of 18 attributes and a maximum of 25, depending upon how many varieties of a configuration were produced.

2.3 VEHICLE ATTRIBUTE DEFINITIONS

The vehicle attributes selected for this study are listed below with their corresponding definitions. The attributes are listed in field order of the data input and are identified by their field numbers and attribute names.

Ol. Vehicle Identification Code

The code to identify the vehicle includes the manufacturer, domestic or import designation, GVWR class, body type, and model year, e.g. General Motors (GM), Domestic (D), 0-6000 lbs. (1), pickup (1), 1974 (74).

02. Model Name, 2-Wheel Drive

The manufacturers designated model name for two wheel drive vehicle, e.g. C-10.

03. Model Name, 4-Wheel Drive

The manufacturers designated model name for 4-wheel drive vehicle, e.g. K-10.

04. Model Name, Cargo Van

The manufacturers designated model name for Cargo Van vehicle, e.g. Tradesman Bl00.

05. Model Name, Passenger Van

The manufacturers designated model name for passenger van vehicle, e.g. Sportsman Bl00.

06. Transmission Type, Number of Gears

Automatic, manual, or semi-automatic and the number of gear ratio changes in forward speed.

07. N/V (std.) (2-Wheel Drive/4-Wheel Drive)

Ratio of engine speed (rpm) divided by vehicle speed (MPH) with standard tires and gearing; first two digits designate N/V for 2-Wheel Drive, and the next two digits designate N/V for 4-Wheel Drive.

08. N/V (std.) (Cargo Van/Passenger Van)

Ratio of engine speed (rpm) divided by vehicle speed (MPH) with standard tires and gearing; first three digits designate N/V for Cargo Vans, and the next three digits designate N/V for Passenger Van.

09. Cubic Inch Displacement

The volume in cubic inches displaced by one piston as it moves from the bottom to the top of its stroke, times the number of cylinders.

10. Number of Engine Cylinders and Arrangement

Number of cylinders and the arrangement in the cylinder block (V, L, or H arrangement) and 8, 6, or 4 cylinders.

R denotes Rotary and the number of chambers is listed. Diesel engine is noted in comments.

11. Compression Ratio

The ratio of maximum volume displaced (volume of a cylinder plus the volume of the combustion chamber) to the minimum volume

(combustion chamber volume).

12. Engine Horsepower

Net horsepower (as defined in SAE standard J 245) is the maximum brake power output of a "fully equipped" engine with all accessories necessary to perform all its intended functions unaided, including, but not limited to, basic built-in components such as intake air system, exhaust system, cooling system, alternator, starter, and emission control equipment.

13. Engine Revolutions per Minute (Horsepower)

The engine revolutions per minute at which engine horsepower is specified.

14. Engine Torque

Net maximum torque in foot pounds of the same "fully equipped" engine as tested for horsepower output.

15. Engine Revolutions per Minute (Torque)

The engine revolutions per minute at which maximum torque is specified.

16. Carburetion and Number of Barrels (STD)

Indicates "Carburetor" (C) and number of barrels on standard engine; or "fuel injection" (FI) if standard.

17. Wheelbase 1

The distance between the centers of the front and rear wheels. The minimum wheelbase for the indicated model.

- 18. Percentage of Sales 1
 - The percentage of a model sold in wheelbase 1 form.
- 19. Wheelbase 2

The distance between the centers of the front and rear

wheels for the next wheelbase configuration over minimum.

20. Percentage of Sales 2
The percentage of a model sold in wheelbase 2 form.

21. Wheelbase 3

The distance between the centers of the front and rear wheels for the longest wheelbase configuration.

- 22. Percentage of Sales 3
 The percentage of a model sold in wheelbase 3 form.
- 23. Curb Weight 1 (1bs.) (2-Wheel Drive/4-Wheel Drive)

The weight of the vehicle in wheelbase 1 form including all standard equipment, spare tire and wheel, all fluids and lubricants to capacity and a full tank of gasoline.

(4 digits for 2-Wheel Drive followed by 4 digits for 4-Wheel Drive)

24. Van Curb Weight 1 (lbs.) (Cargo/Passenger)

The weight of the vehicle in wheelbase 1 form including all standard equipment, spare tire and wheel, all fluids and lubricants to capacity and a full tank of gasoline. (4 digits for Cargo Van followed by 4 digits for passenger van)

25. Curb Weight 2 (lbs.) (2-Wheel Drive/4-Wheel Drive)

The weight of the vehicle as in "Curb Weight 1" except the vehicle is in "Wheelbase 2" form. (4 digits for 2-Wheel Drive followed by 4 digits for 4-Wheel Drive)

26. Van Curb Weight 2 (lbs.) (Cargo/Passenger)

The weight of the vehicle, as in "Van curb weight 1," except the vehicle is in "Wheelbase 2" form.

(4 digits for Cargo Van followed by 4 digits for passenger van)

27. Curb Weight 3 (lbs.) (2-Wheel Drive/4-Wheel Drive).

The weight of the vehicle, as in "Curb Weight 1" except the vehicle is in "Wheelbase 3" form. (4 digits for 2-Wheel Drive followed by 4 digits for 4-Wheel Drive)

28. Van Curb Weight 3 (lbs.) (Cargo/Passenger)

The weight of the vehicle, as in "Van Curb Weight 1,"

except the vehicle is in "Wheelbase 3" form. (4 digits

for cargo van followed by 4 digits for passenger van)

29. GVWR 1

The gross vehicle weight rating in pounds with the vehicle in "Wheelbase 1" form.

30. GVWR 2

The gross vehicle weight rating in pounds with the vehicle in "Wheelbase 2" form.

31. GVWR 3

The gross vehicle weight rating in pounds with the vehicle in "Wheelbase 3" form.

32. Cargo Capacity 1 (ft. 3)

For enclosed trucks, the volume of the enclosed cargo area. If folding or removable seats are provided, the volume is the maximum with seats folded or removed. For open bodied trucks, the bed area multiplied by a height of 6 feet. In either case the vehicle is in "Wheelbase 1" form.

33. Cargo Capacity 2 (ft. 3)

The cargo volume as stated in attribute 32 except the vehicle is in "Wheelbase 2" form.

34. Cargo Capacity 3 (ft. 3)

The cargo volume as stated in attribute 32 except the vehicle is in "Wheelbase 3" form.

35. Number of Passengers

The number of passengers including the driver for which the vehicle was designed and for which normal seating accommodation is provided. For all trucks with variable passenger capacity the minimum and maximum number is listed (2 digits for minimum followed by a dash and 2 digits for maximum).

36. Urban Fuel Economy (MPG)

1975 EPA Federal Test Procedure (FTP) cycle urban fuel ecomony equal to:

- A. For 1974 models, EPA CVS-1 cycle X 1.045* factor.
- B. 1973 and prior models; fuel economy from literature, if available, adjusted to 1975 EPA test level.
- 37. Wheelbase, Fuel Economy

 The wheelbase of the vehicle used for fuel economy data.
- 38. Drive Cycle Urban

 If not EPA CVS-1 will indicate other cycle.
- 39. Highway Fuel Economy (MPG)

1975 EPA cycle urban economy X 1.42* factor for the wheelbase recorded in attribute 37.

- 40. Drive Cycle Highway

 Indicates drive cycle for above.
- 41. Composite Fuel Economy (MPG)

^{*}SAE Technical Report #75057 "Passenger Car Fuel Economy Trends Through 1976" by Austin, Michael and Service.

1975 EPA cycle combination urban-highway fuel economy (weighted 55 percent urban, 45 percent highway) equal to 1975 urban economy x 1.154* factor.

42. Catalytic Converter

Is the vehicle equipped with a catalytic converter?

Yes or No answer.

43. Acceleration Time

Time in seconds, for a vehicle to accelerate from 0 to 40 MPH. If 0 to 40 MPH time is not available, 0 to X is used and X is noted in comments.

**44 Model Production Volume (2-Wheel Drive version)

Production Volume of the 2 Wheel Drive version of the vehicle configuration identified in attribute 01.

**45. Model Production Volume (4-Wheel Drive version)

Production Volume of the 4 Wheel Drive version of the vehicle configuration identified in attribute 01.

**46. Model Production Volume (Cargo Van)

Production Volume of the Cargo Van version of the vehicle configuration identified in attribute 01.

**47. Model Production Volume (Passenger Van)

Production volume of the Passenger Van version of the vehicle configuration identified in attribute 01.

48. List Price (2 Wheel Drive models)

^{*}SAE Technical Report #75057 "Passenger Car Fuel Economy Trends Through 1976" by Austin, Michael and Service.

^{**}NOTE: The production volumes include all similar vehicles represented by the specific vehicle configuration described; i.e., the total for all vehicles listed for a specific model year equals the total of LT manufactured for that model year under 10,000 GVWR.

Base list price of the 2-Wheel Drive vehicle configuration incorporating the described engine and transmission and the most popular Wheelbase.

49. List Price (4-Wheel Drive models)

Base list price of the 4-Wheel Drive vehicle configuration, incorporating the described engine and transmission and the most popular wheelbase.

50. List Price (Cargo Van)

Base list price of the Cargo Van version of the vehicle configuration, incorporating the described engine and transmission and the most popular wheelbase.

51. List Price (Passenger Van)

The base list price of the Passenger Van version of the vehicle configuration incorporating the described engine and transmission and the most popular wheelbase.

52. Highway or Off-Highway (2-Wheel Drive/4-Wheel Drive)

Indicates highway or off-highway configuration, first for the 2-Wheel Drive version and next for the 4-Wheel Drive version. Off-highway vehicles are high chassis height vehicles.

53. Axle clearance (2-Wheel Drive/4-Wheel Drive)

The distance from the bottom of the axle housing to the ground. Two-Wheel Drive first then 4-Wheel Drive.

54. Percentage with Air Conditioning

The rate, for the model indicated in attribute 02, of installation of air conditioning, in percentage of the total production.

55. Air Conditioning Weight (lbs.)

The weight, in pounds, that must be added to the curb weight of the vehicle when air conditioning is installed as a factory option.

56. Cost, Air Conditioning

The cost, in dollars, of the air conditioning option.

57. Percentage with Power Disc Brakes

The rate, for the model indicated in attribute 02, of installation of Power Disc Brakes, in percentage of total production.

58. Power Disc Brakes Weight (lbs.)

The weight, in pounds, that must be added to the curb weight when Power Disc Brakes are installed as a factory option.

59. Cost, Power Disc Brakes

The cost, in dollars, of the Power Disc Brake option.

60. Percentage with Power Steering

The rate of installation of power steering, in percentage of total production for the model indicated.

61. Power Steering Weight (lbs.)

The weight, in pounds, added to the curb weight when power steering is installed as a factory option.

62. Cost, Power Steering

The cost, in dollars, of the power steering option.

63. Percentage with AM Radio

The rate of installation of an AM Radio, in percentage of total production for the model indicated.

64. AM Radio, Weight

The weight, in pounds, added to the curb weight when an AM Radio is installed as a factory option.

65. Cost, AM Radio

The cost, in dollars, of the AM radio option.

66. Percentage with AM/FM Radio

The rate of installation of an AM/FM radio, in percentage of total production for the model indicated.

67. AM/FM Radio, Weight

The weight, in pounds, added to the curb weight when an AM/FM Radio is installed as a factory option.

68. Cost, AM/FM Radio

The cost, in dollars, of the AM/FM Radio option.

69. Percentage with Interior Trim

The rate of installation of a special interior trim option, in percentage of a total production for the model indicated.

70. Cost, Interior Trim

The cost, in dollars, of the special interior trim option.

71. Percentage with Exterior Trim

The rate of installation of special exterior trim options, in percentage of total production for the model indicated.

72. Cost, Exterior Trim

The cost, in dollars, of the special exterior trim option.

73. Percentage with Steel Belted Radial Tires

The rate of installation of Steel Belted Radial tires, percentage of total production for the model indicated.

- 74. Cost, Steel Belted Radial Tires

 The cost, in dollars, of the Steel Belted Radial tire option.
- 75. Percentage with Adjustable Steering

 The rate of installation of Adjustable Steering, in percentage of total production for the indicated model.
- 76. Cost, Adjustable Steering
 The cost, in dollars, of the Adjustable Steering option.
- The rate of installation of Tinted Glass, in percentage of total production for the model indicated.
- The cost, in dollars, of the Tinted Glass option (all windows).
- 79. Comments 1 (maximum 40 characters)

 Clarifying information relating to attribute variations
 or attribute sources.
- 80. Comments 2 (maximum 40 characters)

 Same as attribute 79.

77. Percentage with Tinted Glass

2.4 DATA BASE DEVELOPMENT

78. Cost, Tinted Glass

After the selection of the vehicle configurations to be included in the data base and the attributes used to describe these configurations, the actual collection, collation, and recording of the data on computer tapes occurs.

This process involves:

- 1. Identifying and locating sources of reference material and gathering that reference material.
- 2. Recording data on computer coding sheets.

- 3. Checking doding sheets for accuracy.
- 4. Transferring input data from coding sheets to a key tape. After the data is transferred, it is key verified.
- 5. Processing the keyed data into the Datalog directory system.
- 6. Making formated master list prinout and final checking of data for ommissions, key punch errors, etc.
- 7. Converting Datalog directory output to DOT/TSC tape and master list as required.

2.4.1 Data Research

Data, from published sources, covering specific model configurations, were difficult to obtain for any of the subject data base years. This problem increased in the earliest years. General vehicle specification data were also more difficult to find for the early years of the study. These data gaps were filled through extensive research in Chilton files, the Philadelphia Public Library's Automotive Library, the MVMA files, automotive manufacturers' files, and the manufacturers' advertising agencies files.

In some other cases where data was sparce, some extrapolation was necessary. This occured primarily in 1972-1955 for Chevrolet, IHC, and AMC.

For these manufacturers, the 1973 model configuration percentages were applied to the known 1972 production totals. Engine variants, usage of wheelbase variations, and 4-wheel drive variants were determined by referencing known industry usage during the 1973 period. For the years prior to 1972, Ford model/engine usage was applied to Chevrolet and International known totals to determine vehicle breakouts and wheelbase usage.

Jeep breakouts prior to 1972 were determined by applying current Jeep sales trends, industry trends for the particular model year and some professionsl judgement to known vehicle type production totals.

2.4.2 Fuel Economy

The fuel economy attributes were filled directly from EPA literature for the 1975 to 1977 period where possible. When EPA data was used N/V ratio, weight, body, engine, and transmission combinations were matched as closely as possible to the configuration chosen for the data base.

The urban fuel economy values obtained from the 1973 and 1974 EPA tests were adjusted by multiplying by 1.045* to put them on the 1975 Federal Test Procedure basis which includes cold start and hot start urban test cycles instead of the 1972 test procedures cold start only method.

For 1973 and 1979 the composite city/highway fuel economy value was determined by multiplying 1975 FTP urban fuel economy by 1.154.* The highway fuel economy was determined by multiplying the urban value by 1.42* (which is the sales weighted ratio of highway to urban fuel economy for the 1975 fleet as tested by EPA).

Some road tests were used to supplement available EPA fuel economy information. This was done mostly for the 1972 model year. Though these road tests were sparse, examples were found which indicated that the same truck was tested by more than one magazine. In these cases the various testers achieved similar fuel economy results which creates some confidence in the data.

The fuel economy rating of a light truck has not historically been a very influential characteristic in the prospective purchaser's selection procedure. This, coupled with the fact that road tests data and EPA data correlate very well, indicates that the manufacturers are not inclined, as they are with passenger cars, to supply the testing publications with specially tuned and prepared vehicles.

As a result of this assumption, the road tests data, when used, was recorded as reported by the testing publications.

^{*}Reference: SAE Report #750957 "Passenger Car Fuel Economy Trends Through 1976" by Austin, Michael and Service.

Every effort was made to determine that the road tested vehicle was very similar in weight, type and engine/transmission configuration to the vehicle recorded in the data base.

The fuel economy data available for 1972 LT vehicles were scarce since no EPA data were available and only a few road tests have been performed on LT vehicles. The data available for 1975 Ford LT vehicles was significantly less than other major manufacturers for the 1975 model year. No EPA fuel economy data was available for any year for GVWR values over 6,000 pounds.

The fact that fuel economy is affected by such a wide variety of factors including type of route traveled, vehicle speed, cold start frequency, accessory equipment use, vehicle weight, N/V ratio, transmission type, aerodynamic characteristics, and driver habits, indicates that the fuel economy figures recorded can only serve as a baseline. The many variations cannot be defined in the scope of this research.

The following are the drive cycles used by two publications that road test trucks. The road test cycles of these publications are considered to give reliable information and were referenced for data base information.

1. Motor Trend/Car Life

A 73 mile public road loop, representing approximately 1/3 city, 1/3 suburban and 1/3 highway driving, is used. Maximum speeds do not exceed 60 mph. The tank is filled before and refilled afterwards at the same station. The test loop measures 73.125 miles on a fifth wheel and the testing ambient temperature is 70° to 80°F. The motor is warm at start with no special attempts made to gain fuel economy. The results of this test are considered equal to EPA composite ratings.

2. Popular Science The vehicle is driven steadily at 45 mph around Bridgehampton (Long Island) New York raceway. This is a 2.5 mile

course with many turns and hills intermixed. The test results are considered equal to the EPA composite ratings.

2.4.3 Vehicle Performance

Acceleration times were recorded for 0-40 or 0-60 mph. When the time entered in attribute 43 was 0-60 mph, this was noted in the comments. Very little acceleration time data were found.

It should also be noted that acceleration times would be materially different if the truck were loaded to its capacity.

No attempt was made to assign acceleration times to vehicles for which data was not available. Hence, very little data are recorded in this area.

2.4.4 Correlation of Data

Prior to 1972 maximum horsepower and torque figures were given as gross values in many instances, and since 1972 these figures have been given as net values. The addition of emission equipment, lowering of compression ratios, deemphasis of horse-power ratings and the fact that the net horsepower is more representative of actual available installed horsepower contributed to the change. There is no perfect, direct method of converting from gross to net horsepower rating other than direct comparative testing. However, it was possible to make some comparisons of gross and net horsepower values for the same engines and to develop factors which can be applied to horsepower and torque (separate factors) and note RPM variations for engines of various types, sizes, manufacturers, and configurations.

Comparisons were made, and these correlating values were applied to pre-1972 gross horsepower and torque values to adjust these to net horsepower and torque values. Table 2-5 shows these horsepower and torque factors and variations in RPM.

HORSEPOWER AND TORQUE CORRECTION FACTORS GROSS TO NET HORSEPOWER (GROSS H.P. x FACTOR = NET H.P.) TABLE 2-5.

Engine Type	Horsepower Factor	RPM Reduction or Factor	Torque Factor	RPM Change
4 Cylinder & Rotary Engine	0.89	-200 крм		+200 RPM
6 Cylinder	0.76	3600 RPM and above -400 RPM. Under 3600 RPM use 0.90 factor.	0.80	
8 Cylinder 1.) 315 CID and below Non-High Performance 2.) High performance	0.70	1.) -200 RPM if max. gross HP at 3000 RPM or above.		
- Extra high compression ratio - 5000 RPM max. or more - 225 gross HP or more	0.80	3000 RPM	0.80	-200 RPM
8 Cylinder 1.) 315-350-380 CID 2.) Under 4801 RPM at Gross Horsepower Under 250 Gross Horsepower (up to 360 CID engine) 360 to 380 use judgement as to high		From 4400 to 4800 RPM Gross use 4000 RPM Net Below 4000 to 36000 RPM use: -400 RPM		-
(under 260 horsepower) - Any Two of Above	89.0	below 3600 use 0,90 factor	08.0	200 RPM

HORSEPOWER AND TORQUE CORRECTION FACTORS GROSS TO NET HORSEPOWER (CONTINUED) (GROSS H.P. x FACTOR = NET H.P.) TABLE 2-5.

Engine Type	Horsepower Factor	RPM Reduction of Factor	Torque Factor	RPM Change
8 Cylinder High Performance 1.) 315-350-380 CID 2.) Over 4800 RPM at Gross Horsepower 3.) Over 250 Gross Horsepower (up to 360 CID) 360-380 use judgement as to high performance or not 260 HP or				
above - Any Two of Above	0.80	-200 RPM	0.84	300 КРМ
Rev at Gross Horsepower above 5200 RPM	0.85	-200 кРМ	0.85	-200 RPM
8 Cylinder 1.) 390-460 2.) Under 320 Gross Horsepower 3.) Under 4500 RPM AT Gross Horsepower - Any Two of Above	0.70	Above 3600 RPM use: -400 RPM Below 3600 use 0.90 Factor	0.80	-200 кРМ
8 Cylinder - High Performance 1.) 390 - 460 CID 2.) Over 4500 RPM at Gross Horsepower 3.) Over 330 Gross Horsepower - Any Two of Above	08.0	4800 RPM gross or above use: -400 RPM Under 4800 RPM use: -200 RPM	0.80	3400 RPM or above use: -400 RPM, under 3400 use: -200 RPM
8 Cylinder 460 CID and above, 4500 RPM or less	0.65	-400 RPM	0.76	-400 КРМ

2.5 ATTRIBUTE INFORMATION SOURCES

The following lists (Table 2-6) indicate the sources of information for each attribute.

2.5.1 Delineation of Production Sources

The production figures in this data base are obtained from various sources.

The figures for Ford Motor Company and Chrysler Corporation were obtained directly from the manufacturers and are model year production totals for domestic consumption for all years (1977 to 1955).

Chevrolet/GMC, International Harvester and Jeep figures for the years 1977 through 1973 are model year totals and were obtained from Wards Automotive year books.

Production information for the years 1971 through 1955 is derived from publications of the Motor Vehicle Manufacturers associations for Jeep, Chevrolet/GMC, and International calendar year information obtained from Wards year book and MVMA publications.

The totals for imported light trucks is on a calendar year/ U.S. sale basis and were obtained directly from the importer.

2.5.2 Compatability with Published Information

Occasional disagreement in data may occur between the production figures contained in this report and published production figures due to differences in the scope and time span of the data. For example, calendar year production, calendar year domestic production, total calendar year production, and model year production for domestic consumption, each represents different degrees of information and/or time spans. To further complicate matters, dependent upon the manufacturer, each of these reports may be identical to each other or totally different.

Reporting errors, i.e., supplying an incorrect report to a given publication or typesetting errors, may also cause differences to occur between published production numbers and the production totals supplied in this report.

TABLE 2-6. ATTRIBUTE INFORMATION SOURCE

Attri- bute No.	Attribute Name	Source
01)	Vehicle Identification	Manufacturers' Data Books
02)	Model Name, 2-Wheel Drive	and from
03)	Model Name, 4-Wheel Drive	Manufacturers' Production
04)	Model Name, Cargo Van	Data Information Sheets
05)	Model Name, Passenger Van	sourced from the Manufacturer
06)	Transmission Type, Number of Gears	Manufacturers' Production Data Information Sheets
07)	N/V (STD) (2 Wheel Drive/ 4 Wheel Drive)	Calculated From Information Obtained From Manufacturers' Data Book or in the case of Chevrolet, directly from the Data Book
08)	N/V (STD) (Cargo Van/ Passenger Van)	Calculated from Information Obtained from Manufacturers' Data Books or in the case of Chevrolet, directly from the Data Book
09)	Cubic Inch Displacement	Manufacturers' Production Data Information Sheets and/or Manufacturers Data Books
10)	Number of Engine Cylinders	Manufacturers' Production Data Information Sheets and/or Manufacturers' Data Books
11)	Compression Ratio	Manufacturers' Data Books
12)	Engine Horsepower	Manufacturers' Data Books Automotive Industries

TABLE 2-6. ATTRIBUTE INFORMATION SOURCE (Continued)

Attri- bute No.	Attribute Name	Source
13)	Engine Revolutions per Minute (Horsepower)	Manufacturers' Data Books- Automotive Industries
14)	Engine Torque	Manufacturers' Data Books and Automotive Data Books
15)	Engine Revolutions per Minute (Torque)	Manufacturers' Data Books- Automotive Industries
16)	Carburetion and Number of Barrels (STD)	Manufacturers' Data Books- Automotive Industries
17)	Wheelbase l	Manufacturers' Production Data Information Sheets- Manufacturers Data Books
18)	Percentage of Sales Wheelbase l	Manufacturers' Production Data Information Sheets- Professional judgement based on available information
19)	Wheelbase 2	Manufacturers' Production Data Information Sheets or Manufacturers' Data Books
20)	Percentage of Sales Wheelbase 2	Manufacturers' Production Data Information Sheets- Professional judgement based on available information
21)	Wheelbase 3	Manufacturers' Production Data Information Sheets- Manufacturers Data Books
22)	Percentage of Sales Wheelbase 3	Manufacturers' Production Data Information Sheets- Professional judgement based on available information
23)	Curb Weight 1 (2 Wheel Drive/4 Wheel Drive)	Manufacturers' Data Books
24)	Curb Weight Van l (Cargo/Passenger)	Manufacturers' Data Books
25)	Curb Weight 2 (2 Wheel Drive/ 4 Wheel Drive)	Manufacturers' Data Books.

TABLE 2-6. ATTRIBUTE INFORMATION SOURCE (Continued)

Attri- bute No.	Attribute Name	Source
26)	Curb Weight Van 2 (Cargo/Passenger)	Manufacturers' Data Books
27)	Curb Weight 3 (2 Wheel Drive/ 4 Wheel Drive)	Manufacturers' Data Books
28)	Curb Weight 3 (Cargo- Passenger)	Manufacturers' Data Books
29)	GVWR 1 (Most Popular)	Manufacturers' Production Data Information Sheets- judgements based on infor- mation available
30)	GVWR 2 (Most Popular)	Manufacturers' Production Data Information Sheets- judgement based on infor- mation available
31)	GVWR 3 (Most Popular)	Data Information Sheets- judgement based on infor- mation available
32)	Cargo Volume 1	Manufacturers' Data Books, Edmunds, Calculation
33)	Cargo Volume 2	Manufacturers' Data Book Edmunds, Calculation
34)	Cargo Volume 3	Manufacturers' Data Books Edmunds, Calculation
35)	Number of Passengers	Manufacturers' Data Books, (with normal seating)
36)	Urban Fuel Economy	EPA Literature, Road Test Publications
37)	Wheelbase, Fuel Economy	EPA Literature, Road Test Publications, Judgement
38)	Drive Cycle-Urban	EPA Literature, Road Test Publications
39)	Highway Fuel Economy	EPA Literature, Road Test Publications

TABLE 2-6. ATTRIBUTE INFORMATION SOURCE (Continued)

Attri- bute No.	Attribute Name	Source
40)	Drive Cycle-Highway	EPA Literature, Road Test Publications
41)	Composite Fuel Economy	EPA Literature, Road Test Publications
42)	Catalytic Converter (Yes or No)	Manufacturers' Data Books
43)	Acceleration Time	Road Test and Publications, Edmunds, Manufacturer Spec Sheets
44)	Model Production Volume (2 Wheel Drive)	Manufacturers' Production Data Information Sheets, Wards
45)	Model Production Volume (4 Wheel Drive)	Manufacturers' Production Data Information Sheets, Wards
46)	Model Production Volume (Cargo Van)	Manufacturers' Production Data Information Sheets, Wards
47)	Model Production Volume (Passenger Van)	Manufacturers' Production Data Information Sheets, Wards
48)	List Price (2 Wheel Drive)	Edmunds, Auto News
49)	List Price (4 Wheel Drive)	Edmunds, Auto News
50)	List Price (Cargo Van)	Edmunds, Auto News
51)	List Price (Passenger Van)	Edmunds, Auto News
52)	Highway or Off-Highway (2 Wheel Drive/4 Wheel Drive)	Judgement based on high ground clearance and intended use by manufacturer and government priorities. Based on information obtained from Manufacturers Data Books

TABLE 2-6. ATTRIBUTE INFORMATION SOURCE (Continued)

Attri- bute No.	Attribute Name	Source
53)	Axle Clearance (2 Wheel Drive/4 Wheel Drive)	Manufacturers' Data Books
54)	Air Conditioning, Percentage of Sales	Manufacturers' Data Books
55)	Air Conditioning, Weight	Manufacturers' Data Books
56)	Air Conditioning, Cost	Edmunds
57)	Power Disc Brakes, Percentage of Sales	Manufacturers' Production Data Information Sheets, Wards
58)	Power Disc Brakes, Weight	Manufacturers' Data Books
59)	Power Disc Brakes, Cost	Edmunds
60)	Power Steering, Percentage of Sales	Manufacturers' Production Data Information Sheets, Wards
61)	Power Steering, Weight	Manufacturers' Data Books
62)	Power Steering, Cost	Edmunds
63)	AM Radio, Percentage of Sales	Wards, Manufacturers' Production Data Information Sheets
64)	AM Radio, Weight	Manufacturers' Data Books
65)	AM Radio, Cost	Edmunds
66)	AM/FM Radio, Percentage of Sales	Manufacturers' Production Data Information Sheets, Wards
67)	AM/FM Radio, Weight	Manufacturers' Data Books
68)	AM/FM Radio, Cost	Edmunds
69)	Interior Trim, Percentage of Sales	Wards, Manufacturers' Production Data Information Sheets
70)	Interior Trim, Cost	Edmunds

TABLE 2-6. ATTRIBUTE INFORMATION SOURCE (Continued)

Attri- bute No.	Attribute Name	Source
71)	Exterior Trim, Percentage of Sales	Wards, Manufacturers' Production Data Information Sheets
72)	Exterior Trim, Cost	Edmunds
73)	Steel Belted Radial Tires, Percentage of Sales	Wards, Manufacturers' Production Data Information Sheets
74)	Steel Belted Radial Tires, Cost	Edmunds
75)	Adjustable Steering Percentage of Sales	Wards, Manufacturers' Production Data Information Sheets
76)	Adjustable Steering, Cost	Edmunds
77)	Tinted Glass, Percentage of Sales	Wards, Manufacturers' Production Data Information Sheets
78)	Tinted Glass, Cost	Edmunds
79)	Comments 1	Footnotes relating to other attributes
80)	Comments 2	Footnotes relating to other attributes

2.6 COLLATION AND DATA PROCESSING

Data accumulated during this project were collated and recorded on magnetic tape. Data are delivered on (9) nine track unlabeled tape, at a recording mode or 800 BPI, conforming to 8-bit EBCDIC interchange code. The Structure Definitions Sheet, File Description, Attribute Codes List, Code Tables, and Body Class Definitions are given in Tables 2-7 to 2-11.

TABLE 2-7. STRUCTURE DEFINITION SHEET

- 1. Contract
- 2. Data Title
- 3. Tape ID
- 4. Number of Blocks
- 5. Number of Records

TABLE 2-8. FILE DESCRIPTION (SHEET 1 OF 7)

FILE DE	SCRIPTION	FILE ID. \$ Bypass
FILE NAME LT Historical Dat	a Base	REC. SIZE 445
DISK ORGANIZATION N/A	FILE SEQ. 01	BLOCK SIZE 4450
FIELD TYPES = A-alphanumeric;	I-Integer; R-Re	eal

FLD	SUB	FIELD NAME	POSIT	ION	# OF	FLD	DEC	l .	REMARKS
	FLD	<u> </u>	FROM	TO	BYTES	TYP	POS	ABBR.	
01		Vehicle Ident.Code	1	11	11	A		VID	
		Record #	1	4	4	I			
		Manufacturer	5	6	2	A			See Code Table
		Domestic or Import	7	7	1	A			See Code Table
		GVWR Class	8	8	1	I			See Code Table
		Body Type	9	9	1	I			See Code Table
		Model Year	10	11	2	I.			See Code Table
02		Model Name (2WD)	12	21	10	A		MN2	
03		Model Name (4WD)	22	31	10	A		MN4	
04		(Cargo Model Name Van)	32	41	10	A		MNC	
05		(Pass. Model Name Van)	42	51	10	A		MNP	
06		Transmission Type/# of Gears	52	54	3	A		TR	
	A	Transmission Type	52	52	1	A			
	В	# of Gears	53	54	2	A			
07		N/V STD 2WD/4WD	55	63	9	A		NV4	
	A	N/V STD 2WD	55	58	4	R	1		
	В	Hyphen Separator	59	59	1	A			See Note l
	С	N/V STD 4WD	60	63	4	R	1		
08		(Cargo/ N/V STD Pass. Van)	64	72	9	A		NVV	
	A	N/V STD Cargo Van	64	67	4	R	1		

Note 1: Hyphen Separator (H/S) - Hyphen will separate 2 distinct entries; if field is not present, entire field will be spaces.

TABLE 2-8. FILE DESCRIPTION (SHEET 2 OF 7)

					DESC			•	FILE	ID. \$	Bypass
FILE	NAME_	LT	Hist	orical	Data	Bas	e		REC.	SIZE_	445
DISK	ORGAN:	IZAI	_NOI	N/A	F	ILE	SEQ. 0	1	BLOCE	SIZE	4450
FIELD	TYPE	S =	A-al;	phanumei	cic; I	-Int	eger; 1	R−̀Re	al		

FLD SUB | FIELD NAME POSITION # OF |FLD DEC REMARKS FLD BYTES TYP POS ABBR. FROM TO See В H/S 68 68 A Note 1 1 С 69 72 N/V STD Pass. Van 4 R 09 73 75 Cubic Inch Displac. 3 I 0 CID 10 76 77 Eng. Type/# of Cyl. 2 Α 0 CYL Α 76 76 1 0 Type Α В # of Cylinders 77 77 I 0 1 11 Compression Ratio 78 81 R CR 12 Engine Horsepower 82 84 3 I 0 HP 85 88 13 Horsepower RPM 4 I 0 RPM 14 89 91 3 Ι Engine Torque 0 TOR 15 92 95 Torque RPM 4 Ι 0 RMT 16 Carb. /# of Barrels 96 97 2 ISF Α 0 96 96 Α Carb. Type 0 Α # of Barrels 97 97 В Ι 0 17 Wheelbase 1 98 100 3 I WBl 0 103 3 101 I 18 % of Sales 1 0 PS1 104 1106 19 I 0 WB2 Wheelbase 2 3 107 108 2 Ι % of Sales 2 PS2 20 109 110 21 WB3 Wheelbase 3 3 I 0 112 1113 22 % of Sales 3 PS3

TABLE 2-8. FILE DESCRIPTION (SHEET 3 OF 7)

FILE DESCRIPTION	FILE ID. \$ Bypass
FILE NAME LT Historical Data Base	REC. SIZE 445
DISK ORGANIZATION N/A FILE SEQ. 01	BLOCK SIZE 4450
FIELD TYPES = A-alphanumeric; I-Integer; R-Re	eal

								,	
FLD	SUB	FIELD NAME	POSIT		# OF BYTES		DEC	ABBR.	REMARKS
	FLD	Curb Weight 1	FROM	TO	BITES	TIP	PUS	ABBK.	
23		(2WD/4WD)	114	122	9	A	0	CW1	
	A	Curb Weight 1 (2WD)	114	117	4	I	0		
	В	H/S	118	118	1	A	0		See Note 1
	С	Curb Weight 1 (4WD)	119	122	4	I	0		
24		Curb Weight Van l (Pass./Cargo)	123	131	9	A	0	CIV	
	A	Curb Weight Van l (Cargo)	123	126	4	I	0		
	В	H/S	127	127	1	A	0		See Note l
	С	Curb Weight Van l (Pass.)	128	131	4	I	0 .		
25		Curb Weight 2 (2WD/4WD)	132	140	9	A	0	CW2	
	A	Curb Weight 2 (2WD)	132	135	4	I	0		
	В	H/S	136	136	1	A	0		See Note l
	С	Curb Weight 2 (4WD)	137	140	4	I	0		
26		Curb Weight Van 2 (Cargo/Pass,)	141	149	9	A	0	C2V	
	A	Curb Weight Van 2 (Cargo)	141	144	4	I	0		
	В	H/S	145	145	1	A	0		See Note l
	С	Curb Weight Van 2 (Pass.)	146	149	4	I	0		
27		Curb Weight 3 (2WD/4WD)	150	158	9	А	0	CW3	
	A	Curb Weight 3 (2WD)	150	153	4	I	0		
	B	H/S	154	154	1	A	0		See Note 1
	С	Curb Weight 3 (4WD)	155	158	4	I	0		

TABLE 2-8. FILE DESCRIPTION (SHEET 4 OF 7)

FILE DESCRIPTION	FILE ID. \$ Bypass					
FILE NAME LT Historical Data Base	REC. SIZE 445					
DISK ORGANIZATION N/A FILE SEQ. 01	BLOCK SIZE 4450					
FIELD TYPES = A-alphanumeric; I-Integer; R-Real						

FLD	SUB	FIELD NAME	POSIT	TON	# OF	d.T	DEC		REMARKS
	FLD		FROM	TO	BYTES			ABBR.	102211010
28		Curb Weight Van 3 (Cargo/Pass.)	159	167	9	A	0	C37	
	A	Curb Weight Van 3 (Cargo)	159	162	4	I	0		
	В	H/S	163	163	1	A	0		See Note 1
	С	Curb Weight Van 3 (Pass.)	164	167	4	I	0		
29		GVWR 1	168	171	4	I	0	VWI	
30		GVWR 2	172	175	4	Ι	0	VW2	
31		GVWR 3	176	179	4	I	0	vw3	
32		Cargo Volume l	180	183	4	I,	0	CCl	
33		Cargo Volume 2	184	187	4	I	0	CC2	
34		Cargo Volume 3	188	191	4	I	0	CC3	
35		# of Passengers	192	196	5	A	0	PAS	
	A	Min. #	192	193	2	I	0		
	В	H/S	194	194	1	A	0		See Note 1
	С	Max. #	195	196	2	1	0		-
36	_	Urban Fuel Econ.	197	200	4	R	1	UFE	-
37		Wheelbase/ Fuel Economy	201	203	3	I	0_	WFE	
38		Drive Cycle-Urban	204	216	13	A		DCU	
39		Highway Fuel Econ.	217	220	4	R	1	HFE	
40		Drive Cycle - Highway	221	233	13	A	0	DCH	
41		Composite Fuel Economy	234	237	4	R	1	CFE	

TABLE 2-8. FILE DESCRIPTION (SHEET 5 OF 7)

FILE DESCRIPTION	FILE ID. \$ Bypass
FILE NAME LT Historical Data Base	REC. SIZE 445
DISK ORGANIZATION N/A FILE SEQ. 01	BLOCK SIZE 4450
FIFID TYPES = A-alphanumeric: I-Integer: P-De	221

FLD	SUB	FIELD NAME	POSIT	ION	# OF	FLD	DEC		REMARKS
	FLD		FROM	TO	BYTES	TYP	1	ABBR.	
42		Catalytic Converter	238	240	3	A	0	CAT	
43		Acceleration Time	241	244	4	R	1	ACC	
44		Model Production Volume (2WD)	245	250	6	R	2	MP2	Thousand
45		Model Production Volume (4WD)	251	256	6	R	2	MP4	Thousand
46		Model Production Volume (Cargo)	257	262	6	R	2	MPC	Thousand
47		Model Production Volume (Pass.)	263	268	6	R	2	MPP	Thousand
48		List Price (2WD)	269	273	5	I	0	LP2	
49		List Price (4WD)	274	278	5	I	0	LP4	
50		List Price (Cargo)	279	283	5	I	0	LPC	
51		List Price (Pass.)	284	288	5	I	0	LPP	
52		Highway or Off-Highway	289	295	7	A	0	нон	
	A	HOH - 2WD	289	291	3	A	0		
	В	H/S	292	292	1	A	0		See Note l
	С	HOH - 4WD	293	295	3	A	0		
53		Axle Clearance (2WD/4WD)	296	302	7_	A	0	AC2	
	A	2WD	296	298	3	R	1		
	В	H/S	299	299	1	A	0		See Note l
	С	4WD	300	302	3	R	1		
54		Air Cond. %	303	304	2	I	0	PAC	
55		Air Cond. Weight	305	307	3	I	0	ACW	

TABLE 2-8. FILE DESCRIPTION (SHEET 6 OF 7)

	DESCRIPTION	FILE ID. \$ Bypass					
FILE NAME LT Historical	Data Base	REC. SIZE 445					
DISK ORGANIZATION N/A	FILE SEQ. 01	BLOCK SIZE 4450					
Party Minney 1 - July Talance D. D. J.							

FIELD TYPES = A-alphanumeric; I-Integer; R-Real

FLD	SUB FLD	FIELD NAME	POSIT	TO	# OF BYTES		DEC	ABBR.	REMARKS
56		Air Cond. Cost	308	31.0	3	I	0	CAC	
57		Power Disc Brakes, %	311	312	2	I	0	PDB	
58		Power Disc Brakes,Weight	313	315	3	I	0	PDW	•
59		Power Disc Brakes,Cost	316	318	3	I	0	CPD	
60		Power Steering, %	319	320	2	I	0	PPS	
61		Power Steering, Weight	321	323	3	I	0	PSW	
62		Power Steering, Cost	324	326	3	I	0	CPS	
63		AM Radio %	327	328	2	I	0_	PAM	
64		AM Radio Weight	329	330	2	I	0	AMW	
65		AM Radio Cost	331	333	3	I	0	CAR	
66		AM/FM Radio %	334	335	2	I	0	AFR	
67		AM/FM Radio Weight	336	337	2 .	I	0	AFW	
68		AM/FM Radio Cost	338	340	3	I	0	AFC	
69		Interior Trim %	341	342	2	I	0	PIT	
70		Interior Trim Cost	343	345	3	I	0	CIT	
71		Exterior Trim %	346	347	2	I	0	PET	
72		Exterior Trim Cost	348	350	3	I	0	CET	
73		Steel Belt Tires %	351	352	2	I	0	PSB	
74	·	Steel Belt Tires Cost	353	355	3	I	0	SBC	
75		Adjustable Steering %	356	357	2	I	0	ASP	·

TABLE 2-8. FILE DESCRIPTION (SHEET 7 OF 7)

FILE DESCRIPTION FILE ID. \$ Bypass								ypass	
FILE	FILE NAME LT Historical Data Base REC. SIZE 445								
	DISK ORGANIZATION N/A FILE SEQ. 01 BLOCK SIZE 4450								
	FIELD TYPES = A-alphanumeric; I-Integer; R-Real								
FLD	SUB FLD	FIELD NAME	POSIT	TO	# OF BYTES		DEC POS		REMARKS
76		Adjustable Steering Cost	358	360	3	I	0	ASC	
77		Tinted Glass %	361	362	2	I	0	PTG	
78		Tinted Glass Cost	363	365	3	I	0	CTG	
79		Comments 1	366	405	40	A	0	сом	
80		Comments 2	406	445	40	A	0	CO2	
							·		
_									

TABLE 2-9. ATTRIBUTE CODE LIST (SHEET 1 OF 4)

<u>ATTR</u>	IBUTE NAME	CODE
01)	Vehicle Identification Code	VID
02)	Model Name, 2 Wheel Drive	MN2
03)	Model Name, 4 Wheel Drive	MN4
04)	Model Name, Cargo Van	MNC
05)	Model Name, Passenger Van	MNP
06)	Transmission Type, Number of Gears	TR
07)	N/V (STD) (2 Wheel Drive/4 Wheel Drive)	NV4
08)	N/V (STD) (Cargo Van/Passenger Van)	NVV
09)	Cubic Inch Displacement	CID
10)	Number of Engine Cylinders and Arrangement	CYL
11)	Compression Ratio	CR
12)	Engine Horsepower	HP
13)	Engine Revolutions per Minute (Horsepower)	RPM
14)	Engine Torque	TOR
15)	Engine Revolution per Minute (Torque)	RMT
16)	Carburetion and Number of Barrels (STD)	ISF
17)	Wheelbase 1	WBl
18)	Percentage of Sales 1	PS1
19)	Wheelbase 2	WB2
20)	Percentage of Sales 2	PS2
21)	Wheelbase 3	WB3
22)	Percentage of Sales 3	PS3
23)	Curb Weight 1 (2 Wheel Drive/4 Wheel Drive)	CWl
24)	Curb Weight Van 1 (Cargo/Passenger)	ClV

TABLE 2-9. ATTRIBUTE CODE LIST (SHEET 2 OF 4)

ATTRIBUTE NAME	CODE
25) Curb Weight 2 (2 Wheel Drive/4 Wheel D	rive) CW2
26) Curb Weight, Van 2 (Cargo/Passenger)	C2V
27) Curb Weight 3 (2 Wheel Drive/4 Wheel D	rive) CW3
28) Curb Weight, Van 3 (Cargo/Passenger)	C3V
29) GVWR 1	VWl
30) GVWR 2	VW2
31) GVWR 3	VW3
32) Cargo Volume 1	CCl
33) Cargo Volume 2	CC2
34) Cargo Volume 3	CC3
35) Number of Passengers	PAS
36) Urban Fuel Economy	UFE
37) Wheelbase, Fuel Economy	WFE
38) Drive Cycle - Urban	DCU
39) Highway Fuel Economy	HFE
40) Drive Cycle - Highway	DCH
41) Composite Fuel Economy	CFE
42) Catalytic Converter (If used)	CAT
43) Acceleration Time (0-40 MPH)	ACC
44) Model Production Volume (2 Wheel Drive	e) MP2
45) Model Production Volume (4 Wheel Drive	e) MP4
46) Model Production Volume (Cargo Van)	MPC
47) Model Production Volume (Passenger Var	n) MPP
48) List Price (2 Wheel Drive)	LP2
49) List Price (4 Wheel Drive)	LP4

ATTR	TABLE 2-9. ATTRIBUTE CODE LIST (SHEET 3 OF IBUTE NAME	4) CODE
50)	List Price (Cargo Van)	LPC
51)	List Price (Passenger Van)	LPP
52)	Highway or Off-Highway (2 WD/4 WD)	нон
53)	Axle Clearance (2 WD/4 WD)	AC2
54)	Air Conditioning, Percentage of Sales	PAC
55)	Air Conditioning, Weight	ACW
56)	Air Conditioning, Cost	CAC
57)	Power Disc Brakes, Percentage of Sales	PDB
58)	Power Disc Brakes, Weight	PDW
59)	Power Disc Brakes, Cost	CPD
60)	Power Steering, Percentage of Sales	PPS
61)	Power Steering, Weight	PSW
62)	Power Steering, Cost	CPS
63)	AM Radio, Percentage of Sales	PAM
64)	AM Radio, Weight	AMW
65)	AM Radio, Cost	CAR
66)	AM/FM Radio, Percentage of Sales	AFR
67)	AM/FM Radio, Weight	AFW
68)	AM/FM Radio, Cost	AFC
69)	Interior Trim, Percentage of Sales	PIT
70)	Interior Trim, Cost	CIT
71)	Exterior Trim, Percentage of Sales	PET
72)	Exterior Trim, Cost	CET
73)	Steel Belted Radial Tires, Percentage of	PSB
	Sales	
74)	Steel Belted Radial Tires, Cost	SBC

TABLE 2-9. ATTRIBUTE CODE LIST (SHEET 4 OF 4)

ATTE	RIBUTE NAME	CODE
75)	Adjustable Steering, Percentage of Sales	ASP
76)	Adjustable Steering, Cost	ASC
77)	Tinted Glass, Percentage of Sales	PTG
78)	Tinted Glass, Cost	CTG
79)	Comments 1	COM
80)	Comments 2	CO2

TABLE 2-10. CODE TABLES (SHEET 1 OF 2)

ATTR.

NO. 01) IDENTIFICATION CODE

MANUFACTURERS (Nameplate)	CODE
General Motors Corporation Chrysler Corporation Ford American Motors Corp. (Jeep) International Harvester Corp. Toyo Kogo (Mazda) Nissan (Datsun) Toyota Volkswagen	GM CH FM AM IH TK NI TO VW
POINT OF ORIGIN	CODE
Domestic Imported	D I
GVWR CLASS	CODE
0-6000 6001-8500 8501-10,000 0-6000 + 6001-8500 6001-8500 + 8501-10,000	1 2 3 4 5
BODY TYPE	CODE
Pick-up Suburban Utility Van Multi-Stop	1 2 3 4 5
MODEL YEAR	CODE
1977 to 1955	77 to 55

TABLE 2-10. CODE TABLES (SHEET 2 OF 2)

ATTR. NO. 06) TRANSMISSION TYPE, NUMBER OF GEARS TYPE CODE Manual М Automatic Α Semi-Automatic Over-drive 0 NUMBER OF GEARS CODE 2 3 3 4 4 5 10) NUMBER OF ENGINE CYLINDERS AND ARRANGEMENT ARRANGEMENT CODE L In-line "V" Type V Horizontally Opposed Н R Rotary CODE NUMBER OF CYLINDERS 2 4 4 6 6 8 16) CARBURETION and NUMBER OF BARRELS CODE TYPE Carburetor Fuel Injection

NUMBER OF BARRELS

2

3

CODE

1

3

TABLE 2-11. BODY CLASS DEFINITIONS DOT LIGHT TRUCK DATA BASE

File Code	Body Class	Definition
"1"	Pickup, 2 or 4 Wheel Drive	A conventional truck with a 2 or 4-door cab and an open top cargo carrying bed.
"2"	Suburban, 2 or 4 Wheel Drive	A conventional cab vehicle with extended hood on light truck chassis with passenger and cargo room within the body. A truck version of a passenger station wagon.
"3"	Utility, 2 or 4 Wheel Drive	Any vehicle normally referred to as a rough terrain or "Jeep" type. Vehicle is characterized as having a high ramp breakover angle and very little front and rear overhang. Equipped for off-highway as well as on-highway use.
" 4 "	Van (Passenger or Cargo)	A somewhat rectangular vehicle without the traditional long hood of conventional trucks, having passenger and cargo capacity contained within the body. Has relatively high cargo capacity.
*5"	Multi-Stop	Similar to a Van but much higher and with standard seating capacity limited to 1 or 2 passengers including the driver (i.e. the typical bread van or commercial laundry delivery van). Vehicle has none of the qualities of a passenger car. Is intended, primarily, for low speed intracity delivery.

3. CONCLUSIONS

Data were collected, correlated, and collated for the defined attributes of the applicable physical, operating, performance, and market characteristics of light trucks for the subject model years 1955 through 1977. These vehicle configurations represent the total light truck fleet as sold in the United States in these model years.

Characteristics were documented for over 680 vehicle configurations for all attributes for which information was available or could be reasonably extrapolated from available information. With the addition of this data base, the ability of the Department of Transportation/Transportation Systems Center to understand past and current trends in the light truck market is greatly enchanced. This, coupled with other economic studies, will allow DOT/TSC to predict future trends and possible reactions to outside influences, regulations, etc., that may occur.

₹
•

4. RECOMMENDATIONS

Although this data base combines physical, operating, performance, and market characteristics which are representative of the United States light truck market for 1955 through 1977, the usefulness of the information would be enhanced by expanding the data base coverage. It is recommended that the data base be expanded to include all years, from 1955 to the present. The light truck market has developed rapidly in different areas at different times during this period. The wider base is desirable as it would allow close examination and tracking of the light truck over an expanded period of truck and economic changes.

Other studies which would provide additional insight into the light truck's place in the overall transportation picture would be:

- 1. The uses of light trucks, i.e., commercial, personal recreation or combination.
- 2. The types and magnitudes of loads usually carried in different makes and models of light trucks.
- 3. The effects of cargo load on light truck fuel economy, including a study of operation and load cycles.
- 4. An analysis of the increased use of light truck vehicles to determine which light truck vehicles may be replacing other types of vehicles in the transportation market.
- 5. Identification of the replaced vehicles.

	_
	•
	•

APPENDIX A REPORT OF NEW TECHNOLOGY

This report concerns the collection of existing data on light truck characteristics. Although some extrapolation and/or interpretation of data was used by the contractor as part of the methodology for task completion, no "subject inventions" were achieved during the performance of work on this contract.

		•

HE18.5.A34 nc NHTSA-80-22 Cantwell, C.

Light duty to characterist

FORMERLY FORM DO



U.S. DEPARTMENT OF TRANSPORTATION HESEARCH AND SPECIAL PROGRAMS ADMINISTRATION TRANSPORTATION SYSTEMS CENTER

TRANSPORTATION SYSTEMS CENTER RENDALL SQUARE, CAMBRIDGE, MA. 02142

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE, 8399

PUSTAGE AND FILE PAID
U.S. DEPARTMENT OF TRANSPORTATION
613

